

## Product Specification

### General Description

SFP+ Direct Attach Cables are compliant with SFF-8432 and SFF-8402 specifications. Various choices of wire gauge are available from 30 to 24 AWG with various choices of cable length (up to 7m).

### Features

- Up to 10.3125 Gbps data rate
- Up to 7 meter transmission
- Hot-pluggable SFP 20PIN footprint
- Improved Pluggable Form Factor(IPF)
- compliant for enhanced EMI/EMC
- performance
- Compatible to SFP28 MSA
- Compatible to SFF-8402 and SFF-8432
- Temperature Range: 0~ 70 °C
- RoHS Compatible

### Benefits

- Cost-effective copper solution
- Lowest total system power solution
- Lowest total system EMI solution
- Optimized design for Signal Integrity

### Applications

- 10G Ethernet

### Product Description

The SFP+ passive cable assemblies are high performance, cost effective I/O solutions for 10G Ethernet. SFP+ copper cables allow hardware manufactures to achieve high port density, configurability and utilization at a very low cost and reduced power budget

### High Speed Characteristics

Parameter	Symbol	Min	Typical	Max	Unit	Note
Differential Impedance	TDR	90	100	110	Ω	
Insertion loss	SDD21	-17.04		-3	dB	At 5.15625 GHz
Differential Return Loss	SDD11 SDD22			See 1	dB	At 0.05 to 4.1 GHz
				See 2	dB	At 4.1 to 11.1 GHz
Differential to common-mode return loss	SCD11 SCD22			-10	dB	At 0.2 to 11.1 GHz
Common-mode to common-mode output return loss	SCC11 SCC22			See 3	dB	At 0.01 to 2.5 GHz
				-3		At 2.5 to 11.1 GHz
Channel Operating Margin	COM	3			dB	

Notes:

- 1.Reflection Coefficient given by equation  $SDD11(dB) < -12 + 2 \times \text{SQRT}(f)$ , with f in GHz
- 2.Reflection Coefficient given by equation  $SDD11(dB) < -6.3 + 13 \times \log_{10}(f/5.5)$ , with f in GHz
- 3.Reflection Coefficient given by equation  $SCC11(dB) < -7 + 1.6*f$ , with f in GHz

### Pin Descriptions


#### SFP+ Pin Function Definition

Pin	Logic	Symbol	Name/Description	Notes
1		VeeT	Transmitter Ground	
2	LV-TTL-O	TX_Fault	N/A	1
3	LV-TTL-I	TX_DIS	Transmitter Disable	2
4	LV-TTL-I/O	SDA	Tow Wire Serial Data	
5	LV-TTL-I	SCL	Tow Wire Serial Clock	
6		MOD_DEF0	Module present, connect to VeeT	
7	LV-TTL-I	RS0	N/A	1
8	LV-TTL-O	LOS	LOS of Signal	2
9	LV-TTL-I	RS1	N/A	1
10		VeeR	Reciever Ground	
11		VeeR	Reciever Ground	
12	CML-O	RD-	Reciever Data Inverted	
13	CML-O	RD+	Reciever Data Non-Inverted	
14		VeeR	Reciever Ground	
15		VccR	Reciever Supply 3.3V	
16		VccT	Transmitter Supply 3.3V	
17		VeeT	Transmitter Ground	
18	CML-I	TD+	Transmitter Data Non-Inverted	
19	CML_I	TD-	Transmitter Data Inverted	
20		VeeT	Transmitter Ground	

Signals not supported in SFP+ Copper pulled-down to VeeT with 30K ohms resistor

Passive cable assemblies do not support

LOS and TX\_DIS






*Wuhan GearLink Technology Co.LTD*

## Mechanical Specifications

The connector is compatible with the SFF-8432 specification.



Length (m)	Cable AWG
1	30
2	30
3	30/26
4	26
5	26
7	24

## Regulatory Compliance

Feature	Test Method	Performance
Electrostatic Discharge (ESD) to the Electrical Pins	MIL-STD-883C Method 3015.7	Class 1(>2000 Volts)
Electromagnetic Interference(EMI)	FCC Class B	Compliant with Standards
	CENELEC EN55022 Class B	
	CISPR22 ITE Class B	
RF Immunity(RFI)	IEC61000-4-3	Typically Show no Measurable Effect from a 10V/m Field Swept from 80 to 1000MHz
RoHS Compliance	RoHS Directive 2011/65/EU and it's Amendment Directives 6/6	RoHS 6/6 compliant